

DOCKET No.
XACCTP004

U.S. PATENT APPLICATION
FOR
SYSTEM, METHOD AND COMPUTER
PROGRAM PRODUCT FOR CHARGING FOR
COMPETITIVE IP-OVER-WIRELESS
SERVICES

INVENTOR(S): Limor Schweitzer

ASSIGNEE: XACCT TECHNOLOGIES LIMITED, INC.

KEVIN J. ZILKA
PATENT AGENT
P.O. Box 721120
SAN JOSE, CA 95172

SYSTEM, METHOD AND COMPUTER PROGRAM PRODUCT
FOR CHARGING FOR COMPETITIVE IP-OVER-WIRELESS
SERVICES

5

RELATED APPLICATION(S)

10 The present application claims the priority of a provisional application filed
June 12, 2000 under serial number 60/210,966, and which is incorporated herein by
reference in its entirety. The present application is further related to a co-pending
application filed concurrently herewith under the title "SYSTEM, METHOD AND
COMPUTER PROGRAM PRODUCT FOR PREPAID WIRELESS VOICE
COMMUNICATION AND IP SERVICES" and docket number XACCTP005 and
naming Limor Schweitzer as inventor, and a co-pending application filed
concurrently herewith under the title "SYSTEM, METHOD AND COMPUTER
15 PROGRAM PRODUCT FOR ALLOWING A CARRIER TO ACT AS A CREDIT-
APPROVAL ENTITY FOR E-COMMERCE TRANSACTIONS" and docket
number XACCTP006 and naming Limor Schweitzer as inventor.

20

FIELD OF THE INVENTION

The present invention relates to network accounting, and more particularly to
collecting and processing network accounting information.

25

BACKGROUND OF THE INVENTION

Mobile communication systems have been developed because there has been
5 a need to allow people to move away from fixed telephone terminals without losing
their ability to be reached. While the use of different data transmission services in
offices has increased, different data services have also been introduced into mobile
communication systems. Portable computers enable efficient data processing
wherever a user moves. Mobile communication networks provide a user with
10 efficient access network to actual data networks for mobile data transmission.

Digital mobile communication systems, such as the pan-European mobile
communication system GSM (Global System for Mobile Communication), support
particularly well mobile data transmission. For the GSM, a particular packet mode
15 data transfer service GPRS (General Packet Radio Service) has been developed.

Prior art Figure 1a shows a block diagram of principal components in the
operation of the GPRS system. A packet switching controller SGSN (Serving GPRS
Support Node) controls the operation of packet switching service on the cellular
20 network side. The packet switching controller SGSN controls the sign-on and sign-
off of the mobile station MS, the updating of the location of the mobile station MS
and the routing of data packets to their correct destinations. The mobile station MS
is connected to the base station subsystem BSS through a radio interface Um. The
base station subsystem is connected to the packet switching controller SGSN through
25 the BSS-SGSN interface Gb.

In the base station subsystem BSS, the base station BTS and the base station
controller BSC have been connected to each other by a BTS-BSC interface Abis.
The location of the packet switching controller SGSN in the mobile station network

can vary, for example, according to which technical implementation is being used. Although in Figure 1a, the packet switching controller SGSN has been marked outside the base station subsystem BSS, the packet switching controller SGSN can be placed, for example, as a part of the base station BTS connected to the base station subsystem BSS or as a part of the base station controller BSC.

Prior Art Figure 1b illustrates the various layers of operation of both the mobile station MS and the packet switching controller SGSN. Each layer provides a different function. The International Standardization Organization, ISO, has formulated an OSI model (Open Systems Interconnection) for grouping data transfer into different functional layers. In this model, there are seven layers which are not necessarily needed in all data communication systems.

Transferable information, such as control signaling and data transmitted by the user, between a mobile station MS and a packet switching controller SGSN is exchanged preferably in a data frame mode. The data frame of each layer consists of a header field and a data field. Figure 1b shows also the structure of data frames being used in the GPRS system in different layers.

The information contained in the data field can be, for example, data entered by the user of the mobile station or signaling data. The data field may contain confidential information which has to be secured as reliably as possible before transmitting it to the radio path. In such a case, the encryption has to be executed in such a way that in all simultaneous connections between the packet switching controller SGSN and mobile stations MS connected to it, a separate encryption key is used. Conversely, it is not preferable to cipher the address data of the data frame by the same encryption key used in the ciphering of the data field, since mobile stations MS use a shared radio path resource, i.e. information in many different connections is transferred in the same channel, for example, at different time intervals. In this

case, each mobile station should receive all messages transmitted in the channel concerned and decrypt at least the encryption of the address data to identify to which mobile station the message is intended. Also the packet switching controller SGSN does not know which encryption key should be used.

5

In the following, the operational functions of the layers of the GPRS system have been presented. The lowest layer is called an MAC layer (Media Access Control) which controls the use of the radio path in the communication between the mobile station MS and the base station subsystem BSS, such as allocating channels for transmitting and receiving packets.

10

Data transmission between the base station subsystem and the packet controller SGSN in the lowest level is executed at the L2 layer (link layer) in which link layer protocol is used, such as LAPD protocol according to standard Q.921, frame relay protocol or the equivalent. The L2 layer may additionally contain also quality or routing data according to GPRS specifications. Layer L2 has properties of the physical layer and the link layer of the OSI model. The physical transmission line between the base station subsystem BSS and the packet controller SGSN depends, for example, on where the packet controller SGSN has been located in the system.

15

20

Above the MAC layer, there is an RLC layer (Radio Link Control) and its function is to divide the data frames formed by the LLC layer into fixed sized packets to be transmitted to the radio path and their transmission and retransmission when necessary. The length of the packets in the GRPS system is the length of one GSM time slot (approximately 0.577 ms).

25

LLC layer (Logical Link Control) provides a reliable transmission link between the mobile station MS and the packet controller SGSN. The LLC layer, for

example, adds to the transmitted message error checking data by means of which it is intended to correct those incorrectly received messages and when necessary, the message can be retransmitted.

5 SNDC layer (Sub-Network Dependent Convergence) comprises functions like protocol conversions of transmitted information, compression, segmentation and segmentation of messages coming from the upper layer. Additionally, ciphering and deciphering are accomplished at the SNDC layer. The structure of the SNDC frame has been presented also in Figure 1b. The SNDC frame comprises an SNDC header
10 field (SNDC header) and an SNDC data field (SNDC data). The SNDC header field consists of protocol data (Network Layer Service access point Identity, NLSI) and of SNDC control data, such as determinations of compression, segmentation and ciphering. The SNDC layer functions as a protocol adapter between protocols used at the upper level and the protocol of the LLC layer (link layer).

15 The transmitted information comes preferably as data packets to the SNDC layer from some application, such as messages according to the GPRS system or packets of the Internet protocol (IP). The application can be, for example, a data application of a mobile station, a telecopy application, a computer program which
20 has a data transmission link to a mobile station, etc.

 The MAC layer, RLC layer, LLC layer and the L2 layer contain properties which are described at layer 2 in the OSI model. The above-mentioned layers and the layers described in the OSI model are not, however, distinctly coherent.

25 The SNDC frame is transferred to the LLC layer where an LLC header field is added to the frame. The LLC header field consists of a Temporary Logical Link Identity (TLLI) and an LLC control part. The packet controller GPRS establishes a TLLI identity for each data transmission link between a mobile station MS and a

packet controller GPRS. This data is used in data transmission for defining which data transmission link each message belongs to. Simultaneously, the same TLLI identity can only be used in one data transmission link. After the termination of the link, the TLLI identity used in the link can be allocated to a new link to be subsequently formed. The LLC control part defines the frame number and the command type (info, acknowledge, retransmission request etc.) for ensuring an error free data transfer.

With the various components of a conventional GPRS system of Figures 1a-1b now described, a more comprehensive system will now be disclosed. In particular, Figure 1c illustrates a GPRS system including the various components discussed in Figures 1a-b hereinabove, i.e. SGSN, BSS, etc., in addition to other conventional components. For example, the GPRS system of Figure 1c includes a packet switching controller GGSN (Gateway GPRS Support Node), Home Location Registers (HLRs), Mobile Switching Centers (MSC), Gateway Mobile Services Switching Center (GMSC), Equipment Identity Register (EIR), Mobile Telephone Network (PLMN), Pilot Directory Number (PDN), Switching Center/Visitor Location Register (MSC/VLR), etc.

In addition to the above components of Figure 1c, a billing system 100 is included for charging customers for use of the GPRS system. Traditionally, such billing system 100 interfaces with a CGF (Charging Gateway Framework) which, in turn, interfaces with the SGSN and the GGSN via a conventional interface, Ga.

The prior art billing system 100 collects information from the GPRS equipment. Such information often takes the form of call description records (CDRs). CDRs traditionally provide a record of called numbers, and a date, time, length and so on of each telephone call. In use, the approach takes the GPRS CDRs,

collects them into the CDF, does some processing (such as mapping call-start with call-end) and sends the CDRs to the billing system 100.

Unfortunately, such CDRs received from the GPRS equipment are
5 insufficient in terms of allowing monitoring of the content of the traffic.
Accordingly, the CGF does not allow for network accounting based on content.
Content-based network accounting involves the collection of various types of
information during users' communications over a network. Examples of such
network accounting information may include, but is not limited to a session's source,
10 destination, user name, duration, time, date, type of server, volume of data
transferred, etc. Armed with such accounting information, various services may be
provided that require network usage metering of some sort.

There is therefore a need for a technique of performing network accounting
15 and charging for content usage in a wireless network environment.

DISCLOSURE OF THE INVENTION

5 A system, method and computer program product are provided for charging
for Internet Protocol (IP) usage utilizing a wireless network. Initially, call
description record information is received from a wireless network in real-time.
Such call description record information is associated with customer communication
over the wireless network. Further collected in real-time is IP content usage
information associated with the transmission of content using an IP during the
10 customer communication. The customer is then charged for the customer
communication utilizing the call description record information and the IP content
usage information.

15 In one embodiment of the present invention, the call description record
information may be received from a general packet radio service (GPRS) system.
Optionally, fraud and quality of service may be monitored utilizing the call
description record information and the IP content usage information.

20 In another embodiment of the present invention, the customer may be
charged for the customer communication based on time data of the call description
record information. Further, the customer may be charged for the customer
communication based on volume data of the call description record information. As
an option, the customer may be charged for the communication by mapping the IP
content usage information to the call description record information.

25

In another aspect of the present invention, a system, method and computer
program product may be provided for altering service over a wireless network based
on an IP address. In particular, a call may be received from a mobile communication
unit utilizing a wireless network. Such mobile communication unit has an IP address

associated therewith. Thereafter, the IP address associated with the mobile communication unit is identified. By this design, a service over the wireless network may be altered based on the IP address.

- 5 In one embodiment of the present aspect of the invention, the service may be altered by altering a quality of service of the call, altering an access provided to the mobile communication unit during the call, and/or altering a prioritization of the call.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
22

BRIEF DESCRIPTION OF THE DRAWINGS

5 Prior art Figure **1a** shows a block diagram of principal components in the operation of a General Packet Radio Service (GPRS) system;

 Prior Art Figure **1b** illustrates the various layers of operation of both the mobile station (MS) and the packet switching controller (SGSN) of the GPRS
10 system;

 Prior Art Figure **1c** illustrates a GPRS system including the various components discussed in Figures **1a-b** hereinabove in addition to other conventional components;
15

 Figure **2** shows an accounting system in accordance with one embodiment of the present invention and the manner in which it interfaces with the GPRS system;

 Figure **3** illustrates a method of collecting information for the purpose of
20 charging for Internet Protocol (IP) usage utilizing a wireless network;

 Figure **4** is an illustration of one example of mapping the IP content usage information to the call description record information;

25 Figure **5** illustrates a network system configured in accordance with one embodiment of the present invention;

 Figure **6** illustrates a method for altering service utilizing a wireless network based on an IP address; and

Figure 7 shows a schematic of a system for altering service utilizing a wireless network based on an IP address in accordance with the method of Figure 6.

SECRET

DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 Figures **1a-1c** illustrate the prior art. Figure **2** shows an accounting system **200** in accordance with one embodiment of the present invention and the manner in which it interfaces with a General Packet Radio Service (GPRS) system **202**. The system **200** includes a plurality of data gatherers **204** which are in turn a component of a plurality of information source modules (ISMs). Such ISMs interface with the
10 Serving GPRS Support Node (SGSN) and Gateway GPRS Support Node (GGSN) of the GPRS system **202** for receiving the call description records (CDRs) therefrom.

 This may be accomplished by receiving CDRs directly from the SGSN and/or GGSN. Also, the present invention may support the Ga protocol as described by
15 European Telecommunications Standards Institute (ETSI) specs, accepting all types of CDRs produced by SGSN and GGSN. This provides mobility, short message service (SMS), and quality of service (QoS). It should be noted, however, that the accounting system **200** may interface the GPRS system by any desired means. The accounting system **200** may monitor all the traffic (e.g. user traffic,
20 control/management traffic, network signaling, etc.) carried over any interface in the GPRS system. This enables the accounting system **200** to collect real-time information associated with customer communication over the wireless network as well as IP content usage.

25 As will soon become apparent, the system **200** uses the received CDRs to map IP content events to ISMs, resulting in a new type of call description records, XDRs. Such XDR's get fed into rating engines and then to a standard content based billing module **206**. It should be noted that as real-time information is gathered by the system **200**, various services can be provided based on collected information; e.g.

billing, fraud detection, pre-paid service, QoS monitoring, network performance based dynamical provisioning, etc. For more information on how one exemplary content based billing module **206** operates, reference may be made to PCT application WO9927556A2 entitled "NETWORK ACCOUNTING AND BILLING SYSTEM AND METHOD" published June 3, 1999, and which is incorporated herein by reference in its entirety. The present invention thus uses GPRS CDRs in a non-conventional way, mixing them with IP content usage records before feeding them to billing and customer care systems.

Figure **3** illustrates a method **300** of collecting information for the purpose of charging for Internet Protocol (IP) usage utilizing a wireless network. Initially, in operation **302**, call description record information is received from a wireless network. Such call description record information is associated with customer communication over the wireless network.

In one embodiment, the call description record information may include conventional CDRs or any other data structure that is collected from the GPRS system, and is descriptive of calls that take place thereover. Further, the call description record information may be collected in real-time by the data gatherers **204** of the ISMs, which interface the GPRS system **202** through any GPRS internal interfaces or functional modules. Note Figure **2**. In one embodiment, the receipt of the CDRs from the GPRS prompts operation by the gatherers **204** of the ISMs. It should be noted that the call description record information may include any data structure that is collected from a wireless network and is descriptive of calls that take place on such network.

Further collected in real-time is IP content usage information associated with the transmission of content using an IP during the customer communication. Note operation **304**. The IP content usage information may identify the IP usage

associated with the transmission of the content. In use, such content usage information may be collected in real-time and include, but is not limited to a session's source, destination, user name, duration, time, date, type of server, volume of data transferred, and/or information on any other parameter(s) related to communication using the Internet Protocol. Armed with such accounting information, various services may be provided that require network usage metering of some sort.

Next, in operation 306, the customer is then charged for any aspect of the customer communication utilizing the real-time call description record information and the Internet Protocol content usage information. As an option, the customer may be charged for the communication by mapping the Internet Protocol content usage information to the call description record information. This mapped information is then sent to the billing module 206. Further, the mapped information may be filtered, enhanced, and/or aggregated prior to being delivered to the billing module 206.

The present invention thus enables charging for competitive IP-over-wireless services, based on usage events that are a cohesion of IP content usage records with CDRs generated by a wireless network. Additional information relating to the mapping process will be set forth in greater detail during reference to Figure 4. As an option, the customer may be charged for the communication based on time, volume, or APN data of the call description record information. Further, fraud, churn and quality of service may be monitored utilizing the call description record information and the Internet Protocol content usage information.

It should be noted that multiple instances of the GPRS ISM can co-exist, thus providing scalability, fault-tolerance, and redundancy. One embodiment of the present invention enables the replacement of a vendor-dependent charging gateway

with ISM's. This provides for ease interoperability among different GPRS equipment, and GPRS/IP convergence mediation functionality.

Figure 4 is an illustration of one example of mapping the Internet Protocol content usage information to the call description record information. As shown, a probe 400 collects source and destination IP addresses, application information, an amount of sent and received data, start and end timestamps, and effective quality of service. Further provided is a GPRS Data Enhancement Module (DEM) 402. The DEM 402 stores a table in memory that is used to associate dynamic IP flow with International Mobile Station Identity (IMSI), cellular and quality of service. This is mapped to a Lightweight Directory Access Protocol (LDAP) 404 and aggregated with an aggregator 406. Resulting are contract records 408.

The Lightweight Directory Access Protocol (LDAP) has emerged as an Internet Engineering Task Force (IETF) open standard to provide directory services to applications ranging from e-mail systems to distributed system management tools. LDAP is an evolving protocol that is based on a client-server model in which a client makes a TCP/IP connection to an LDAP server, sends requests, and receives responses. The LDAP information model, in particular, is based on an "entry", which contains information about some object. Entries are typically organized in a specified tree structure, and each entry is composed of attributes. LDAP provides the capability for directory information to be queried or updated. It offers a rich set of searching capabilities with which users can put together complex queries to get desired information from a backing store.

25

Same information sources can be used to create multiple types of usage records in order to bill for various types of services or to be used by various BSSs. As such, the information residing at 400 that may be collected through NetFlow, Remote Traffic Monitoring (RMON), web and e-commerce events gets further

enhanced by a GPRS Associator. Further, synchronization is provided between distributed (geographically dispersed) associators, and competitive content-based tariff models may be created.

5 Figure **5** illustrates a network system **500** configured in accordance with one embodiment of the present invention. As shown, a mobile IP-enabled device **502** is coupled to a router **504** which, in turn, is coupled to a wide area network **506**. In a layer-3 or layer-7 Virtual Private Network (VPN), it is possible to efficiently allocate communication resources for packets belonging to specific applications or IP
10 addresses. GPRS APN is basically a layer-2 VPN which means allocating a dedicated data channel is possible even if it is not fully used or meets the needs of the application used by the user.

 Figure **6** illustrates a method **600** for altering service over a wireless network
15 based on an Internet Protocol (IP) address. In particular, a call may be received from a mobile communication unit utilizing a wireless network in operation **602**. It is important to note that each mobile communication unit or group thereof has at least one IP address associated therewith. Such IP address may be assigned or allocated in a contract, and accomplished by provisioning of a LDAP(Radius) server.

20 Such mobile communication units may include any type of mobile unit including but not limited to, cellular phones, lap top computers, personal digital assistants(PDAs), palm computers, etc. These mobile units may or may not employ cellular technology for providing the wireless environment.

25 Thereafter, in operation **604**, the IP address associated with the mobile communication unit is identified. By this design, service over the wireless network may be altered based on the IP address. Note operation **606**.

It should be noted that the service may be altered in any desired manner. For example, a quality of service (QoS) and/or cost of service (CoS) of the call may be altered. Further, an access provided to the mobile communication unit during the call may be altered. For example, a mobile communication unit may be selectively precluded from accessing a corporate network and/or a publicly available wide area network (WAN), i.e. the Internet. In particular, certain address groups may only access corporate network, other addresses may only access the Internet, and still other addresses may access both. Still even other addresses may receive QoS commitment when accessing corporate network.

10

As an option, the service may be altered by prioritizing calls to and from the mobile communication unit. Configuration of network equipment may be required to allow prioritization of packet flows based on IP address source and destination. During use, a mobile communication unit assigned a higher priority would receive faster service since it would be serviced before units with a lower priority.

15

It should be noted that the foregoing factors may be set forth in a contract agreed upon at an earlier date. Further, Orchestream (IPHighway, CISCO QPM, etc) can provision network equipment to exhibit these features.

20

Figure 7 shows a schematic of a system **700** for altering service utilizing a wireless network based on an IP address in accordance with the method **600** of Figure 6. As shown a plurality of IP-enabled mobile communication units **702** are provided which are adapted to connect to a base station BSS **704** over a Global System for Mobile Communication (GSM) **706** or any other wireless network.

25

A packet tunnel **708** is then created from the handset through a SGSN of the BSS **704** to a router **710** logically located in the GGSN. From that router **710**, the

packets are outputted to the operator's IP network **712**. It should be noted that the customer is connected to the operator through an E1 link.

5 The IP routers and IP backbone switches are provisioned so that packets that originate from handsets with certain IP addresses and/or are destined to IP addresses that relate to the customer's corporation, are given higher priority. This creates a "better experience" for the corporate mobile customer, when he or she communicates with the office. Such customer can still browse the Internet and those packets go out through the ISPs to which that operator is linked. These ISPs do not necessarily
10 provide QoS guarantees.

A LDAP Radius server **714** may be provisioned so that whenever mobile communication units belonging to these corporate customers "log-in" to the network, they will be given an IP address that exhibits the QoS guarantees described above.
15 The present invention may collect the accounting information from the different parts of the network, correlating GPRS info with IP content in the manner set forth hereinabove. Customer care system can provision the converged network through the present invention. Converged data records may then be sent from the present invention to be rated and then sent to other systems such as an "E-Wallet" (prepaid
20 system). For more information on such system, reference may be made to a co-pending application filed concurrently herewith under the title "SYSTEM, METHOD AND COMPUTER PROGRAM PRODUCT FOR PREPAID WIRELESS VOICE COMMUNICATION AND IP SERVICES" and docket number XACCTP005 and naming Limor Schweitzer, and which is incorporated herein by
25 reference in its entirety.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of a preferred embodiment should not be

limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

[illegible]